



TRAFFIC CONTROL LEGEND

1. TYPE III BARRICADES AND ROAD CLOSURE SIGNS SHALL BE POSITIONED AS SHOWN, IN ACCORDANCE WITH HIGHWAY STANDARD 701901, THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, AND AS DIRECTED BY THE ENGINEER.
2. TYPE A LOW INTENSITY FLASHING LIGHTS SHALL BE USED ON THE FIRST SIGN IN ADVANCE OF THE WORK SITE AND TYPE III BARRICADES DURING HOURS OF DARKNESS.
3. ALL WARNING SIGNS SHALL BE A MINIMUM OR 48" x 48" AND HAVE A BLACK LEGEND AND BORDER ON A FLUORESCENT ORANGE REFLECTORIZED BACKGROUND.
4. EXACT LOCATION OF WARNING SIGNS AND BARRICADES SHALL BE STAKED IN THE FIELD FOR APPROVAL BY THE ENGINEER PRIOR TO INSTALLATION.
5. THE CONTRACTOR SHALL MAINTAIN ACCESS TO ENTRANCES AT ALL TIMES.
6. SEE HIGHWAY STANDARDS 701801 AND 701901 FOR ADDITIONAL TRAFFIC CONTROL GUIDELINES.
7. AT NO TIME SHALL THE COMPLETE CLOSURE OF THE GATEWAY IMPRESSION'S ENTRANCE ALONG IL-162 STREET BE PERMITTED.

TRAFFIC CONTROL LEGEND

-  DETOUR ROUTE
-  WORK AREA
-  TYPE III BARRICADES
-  TYPE A LOW INTENSITY FLASHING LIGHTS
-  TRAFFIC CONTROL SIGN
-  IL - 162 EAST 24" x 8"

-  W20-3 (48" x 48") FLUORESCENT ORANGE
-  W20-3 (48" x 48") FLUORESCENT ORANGE
-  BARRICADE AHEAD

TRAFFIC CONTROL SIGNAGE

-  SPECIAL (24" x 24") FLUORESCENT ORANGE
-  SPECIAL (24" x 24") FLUORESCENT ORANGE
-  R-11-2 (60" x 30") (WHITE)
-  R-11-4 (60" x 30") (WHITE)
-  DETOUR LEFT M4 - 9L (0) 30" x 24"
-  DETOUR RIGHT M4 - 9R (0) 30" x 24"
-  DETOUR STRAIGHT M4 - 9S (0) 30" x 24"
-  END DETOUR M4 - 8a (0) 24" x 18"

FILE NAME = 19045 - DESIGN.DWG



USER NAME =	SAM WRIGLEY	DESIGNED -	---	REVISED -	---
PLOT SCALE =	1" = 1'	DRAWN -	---	REVISED -	---
PLOT DATE =	2019-12-13	CHECKED -	---	REVISED -	---
		DATE -	2019-07-03	REVISED -	---

CITY OF TROY
116 EAST MARKET STREET
TROY, IL 62294

TRAFFIC CONTROL PLAN

SCALE:	SHEET NO.	OF SHEETS	STA.	TO STA.
--------	-----------	-----------	------	---------

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
		MADISON	7	x
WEST CLAY STREET SEWER RECONSTRUCTION CITY OF TROY				